



## 400Hz High Performance Single Jacket SMART Cable Assemblies

Your CONDUIT to Performance.™






PAGE's modular SMART single jacket high performance six around one cable assemblies provide the finest features in the industry today. From our molded on head with rugged strain relief to our quick change single piece 6 pole HARDHEAD™ plug, our 400Hz cable assemblies set the new standard! The robust design ensures long life on the ramp and the built-in safety features provide an extra level of insurance to protect operators and the aircraft being serviced. Once you try the PAGE SMART cables you'll know why they say...

**"It doesn't get any better than this."**



P5000 (Green) with thermal overload protection and P5001 (orange) standard HARDHEAD™ replaceable plug heads.


### Performance Features

-  Rugged HARDHEAD™ replaceable single piece plug head, built to withstand the harsh ramp environment.
-  Built-in thermal protection device to detect and disconnect output power in an overtemp situation.
-  Built-in Lost Neutral Detection will disconnect output power should the cables neutral conductor break.
-  Modular design with replaceable sealed modular control switches for quick changes on the ramp.
-  Molded strain relief provides added strength for longer service life.

Only PAGE's SMART Aircraft Ground Power Cables offers redundant thermal protection in the HARDHEAD™ plug and in the connector, AND lost neutral protection making this **the safest cable assembly available.**

### Specifications

Power Conductors	6 each AWG #4
Neutral Conductor	1 each AWG #1
Control Conductors	4 x 3 AWG #18
Control Conductors	2 x TP AWG #18
Voltage Rating	600 VAC
Current Rating	260 Amperes
Temperature Range	-55C to 90C
Diameter	1.65 inches
Bending Radius	10 inches
Voltage Unbalance	.02 Volts *
Voltage Drop	2.1 Volts*
Weight Per Foot	2.10 lbs.
Jacket Material	Reinforced Neoprene



Cross Section Shown

\* at 90kVA, 0.8 power factor on 60 foot cable.

[WWW.PAGEINDUSTRIES.COM](http://WWW.PAGEINDUSTRIES.COM)

TOLL FREE 1-855-465-PAGE  
(1-855-465-7243)

PHONE 1-707-469-7243

FAX 1-707-469-7244

EMAIL SALES@PAGEINDUSTRIES.COM

**PAGE GSE**

2050 CESSNA DRIVE  
VACAVILLE, CA 95688  
USA



## PAGE 400Hz Single Jacket Power Cable Assembly Ordering Information Chart

PT	25	10	—	60	SG
↑	↑	↑		↑	↑
Nose Type	Connector type	Cable Type		Cable Length in feet	Configuration Suffix

### Nose Type

<b>PT</b>	Standard thermally protected replaceable contact section. (Part #P5000)
<b>PN</b>	Replaceable contact section, no thermal protection. (Part # P5001)
<b>PF</b>	Replaceable contact section with 2 part F pin. Built to MIL-DTL-32180. (Part # P5010)
<b>PM</b>	Molded on 400Hz plug. No replaceable contact section. Built to MS25486.
<b>PA</b>	Attachable 400Hz plug. No replaceable contact section. Built to MS25486.

### Connector type

<b>20</b>	400Hz ground power cable with replaceable contact section not wired for switch modules.
<b>21</b>	400Hz ground power cable with replaceable contact section. Wired for ON/OFF and Motions switches. Blank modules installed.
<b>22</b>	400Hz ground power cable with replaceable contact section. Wired for ON/OFF switch module only.
<b>23</b>	400Hz ground power cable with replaceable contact section. Wired for MOTION switch module switch only.
<b>24</b>	400Hz ground power cable with replaceable contact section. Wired for OFF / power 'ON' LED switch module.
<b>25</b>	400Hz ground power cable with replaceable contact section. Wired for ON/OFF, and MOTION switches modules.
<b>26</b>	400Hz ground power cable with replaceable contact section. Wired for OFF / power 'ON' LED and MOTION switch modules.

### Cable Type

<b>10</b>	400Hz Single Jacket 260Amp six around one with center neutral.
<b>11</b>	400Hz Single Jacket 180Amp six around one with center neutral. Built to MIL-DTL-32180 Standards.

### INDIVIDUAL COMPONENTS

<b>P5000</b>	Replaceable contact section with built-in thermal protection. Standard.
<b>P5001</b>	Replaceable contact section without thermal protection.
<b>P5002</b>	ON/OFF pushbutton switch module. (Add "-NO" for normally open OFF switch)
<b>P5004</b>	Motion pushbutton switch module. (Extend and retract power cable)
<b>P5005</b>	BLANK module.
<b>P5006</b>	OFF/LED "PWR ON" switch module. (Add "-NO" for normally open OFF switch)
<b>P5010</b>	Replaceable contact section with 2 Part F Built to MIL-DTL-32180 standards.