

PCAir WYE Split Duct Assemblies

Your CONDUIT to Performance.™

We offer a complete line of flexible ducting products designed to meet your industrial heating, cooling and ventilation requirements. Specialty fabrics are selected for products capable of handling varying temperatures of air.

Applications include industrial, commercial and residential work area climate control, equipment heating, special events, drying, construction curing and more.



AVAILABLE FABRICS	
TEMPERATURE	FABRIC
-40 to 200°F	White, Yellow or Black PVC
-65 to 375°F	Yellow TR
-65 to 500°F	Grey HT
STANDARD CONFIGURATIONS	
INLET DIA.	OUTLET DIA.
INLET DIA.	OUTLET DIA.
INLET DIA.	OUTLET DIA. 16" / 16"
16" 16"	OUTLET DIA. 16" / 16" 12" / 12"
16" 16" 20.7"	OUTLET DIA. 16" / 16" 12" / 12" 20.7" / 20.7"

Features:

- Splits one length of duct into two sections.
- Diameter Range: 8" to 24" (contact factory for custom sizes).
- Lock-stitch sewn construction.
- Standard configuration includes strap inlet and end ring outlets.
- Straight Wye The inlet is sized the same as the outlets.
- Transition Wye Tapers to smaller or larger diameters.
- Folds flat for storage and transportation.
- Ideal for supply air applications.

WWW.PAGEINDUSTRIES.COM

TOLL FREE I-855-465-PAGE (I-855-465-7243)

PHONE I-707-469-7243

FAX I-707-469-7244

EMAIL SALES@PAGEINDUSTRIES.COM

PAGE GSE

2050 CESSNA DRIVE VACAVILLE, CA 95688

