

Air Start Hose & Couplings

Your CONDUIT to Performance."

PAGE provides a full line of the finest quality pneumatic air start hose assembles and coupling in the industry that meets or exceeds the highest standards required by major aircraft operators and equipment purchasers



Commercial Pneumatic Air Start Hose

Temperature Range: -80 degrees F to +500 degrees F

Operating Pressure: 100psi
Proof Pressure: 250psi

Commercial Pneumatic Air Start Scuff Jackets

- Braided Scuff Cover: One piece integral, braided, high-tensile Dacron® scuff cover as used by the military, maintains integrity in the most abusive environments.
- Leno Weave Scuff Cover: Economical alternative available upon request.

Part Number Description

PAS30* Air start hose and leno weave scuff jacket

PAS31* Air start hose only
PAS32* Air start scuff jacket only

* First number designates length. 30' part number shown.

Hose and Scuff Jackets come in 30', 40', 50' and 60' lengths.

3 1/2" I.D. hose and 4 1/4" I.D. scuff cover



93 Series Air Start Couplings

- ♦ Positive "Lock" and "Unlock" positions
- Semi-circle handle can be indexed for additional clearance in all aircraft panels
- Field tested with positive results.
- ♦ Three separate locking features.

PV7950-93-134 PV7950-93-154 PV7950-93-114



PV0002-0048-(XX)



PV7950-93-134 Coupler mated to Air Start hose

WWW.PAGEINDUSTRIES.COM

TOLL FREE I-855-465-PAGE (I-855-465-7243)

PHONE I-707-469-7243

FAX I-707-469-7244

EMAIL SALES@PAGEINDUSTRIES.COM

PAGE GSE

2050 CESSNA DRIVE VACAVILLE, CA 95688 USA

